



DFRB-060-E

desiccant rotor air dehumidifier




technical data

Process/Dry Air Flow	680/500	Nm ³ /h
Available Pressure For Ducting	150	Pa
Reactivation Air Flow	180	Nm ³ /h
Available Pressure For Ducting	100	Pa
Nominal Drying Capacity (*)	2,7	kg/h
Total Power Supply	3,6	Kw
Motors Power	0,19	Kw
Reactivation Heater Power	3,41 (nominal) 6 (maxim)	Kw
Electrical Supply	400V/III+N/50Hz	

09/04 F-1001-01/B

(*) Nominal capacity: 20°C and 60% R.H.

capacity diagram (*)



Settled Parameters:

- Process/Reactivation Air Temperature: 20 °C
- ΔT Reactivation Heater According To Nominal Power
- Equal Process/Reactivation Air Moisture Content

(*) At other operating conditions, pls. ask for the corresponding performances




specification

Air dehumidifier by high performance desiccant silicagel rotary element, brand FISAIR, model DFRB-060-E:

- Self-supporting stainless steel sheet housing, easily serviceable.
- Air intake with G4 filter mat, centrifugal simple ear air fan with direct motor drive.
- Rotary desiccant element driven by gear motor, teeth pulley and transmission belt, with three front sections; for dry, heat recovery and wet air streams.
- Partition and peripheral contact-type airseals.
- Dessicant reactivation air heater PTC-type, with self limited operation temperature.
- Process inlet, dry and wet outlets; with round connectors with rubber seals.
- On-off switch with on-light. Line breaker switch.
- Operation Ampere gage.
- Performance, airflows and other data as per front page.

overall dimensions



Remark: - Approx. weight: 66 kg
- All dimensions in mm